

SPRINKLER PIPE

Trust Bull Moose when it comes to protecting your most valuable assets.

As the leading manufacturer of steel sprinkler pipe, we understand that there are no second chances in fire suppression. You need products of enduring quality and exceptional strength-plus reliable service. You need Bull Moose.

BULL MOOSE ADVANTAGES:

- UL listed (US & Canada) and FM approved
- ASTM A135 and A795 Type E, Grade A Certified
- Complies with NFPA-13, 13R and 14
- Industry-leading hydraulic characteristics.
- CRR of 1.0 and greater
- All pipe NDT weld tested

Exclusive maker of Reddi-Pipe® red painted pipe.

OTHER BENEFITS/SERVICES:

- We have the most stocking locations in industry, for best delivery and availability
- Plain end or roll groove
- Eddy Guard II® bacterial-resistant internal coating
- Custom length options
- Hot dipped galvanization
- Reddi-Pipe® red pipe to eliminate field painting
- Compatible for use in wet, dry, preaction and deluge sprinkler systems











800.325.4467 sales@bullmooseindustries.com BullMooseTube.com

	Bull Moos	e Fire Sp	orinkle	er Pipe	Produ	ıct Info	ormati	ion		
Nominal Pipe Size (Inches)		1"	1-1/4"	1-1/2"	2"	2-1/2"	3"	4"	6"	8"
EDDY FLOW	0.D. (in)		1.660	1.900	2.375	2.875	3.500	4.500		
	I.D. (in)		1.530	1.728	2.203	2.705	3.334	4.310		
	Empty Weight (lb/ft)		1.222	1.844	2.330	2.809	3.361	4.968		
	Water Filled Weight (lb/ft)		2.019	2.860	3.982	5.299	7.144	11.290		
	C.R.R.		1.98	3.44	2.78	1.66	1.00	1.00		
	Pieces per Lift		61	61	37	30	19	19		
	Lift Weight (lbs) 21' lengths		1,565	2,362	1,810	1,770	1,341	1,982		
	Lift Weight (lbs) 24' lengths		1,789	2,700	2,069	2,022	1,533	2,265		
	Lift Weight (lbs) 25' lengths		1,864	2,812	2,155	2,107	1,596	2,360		
SCHEDULE 10	0.D. (in)	1.315	1.660	1.900	2.375	2.875	3.500	4.500	6.625	8.625
	I.D. (in)	1.097	1.442	1.682	2.157	2.635	3.260	4.260	6.357	8.249
	Empty Weight (lb/ft)	1.410	1.810	2.090	2.640	3.530	4.340	5.620	9.290	16.940
	Water Filled Weight (lb/ft)	1.820	2.518	3.053	4.223	5.893	7.957	11.796	23.038	40.086
	C.R.R.	15.27	9.91	7.76	6.27	4.92	3.54	2.50	1.158	1.805
	Pieces per Lift	91	61	61	37	30	19	19	10	7
	Lift Weight (lbs) 21' lengths	2,695	2,319	2,677	2,051	2,224	1,732	2,242	1,951	2,490
	Lift Weight (lbs) 24' lengths	3,079	2,650	3,060	2,344	2,542	1,979	2,563	2,230	2,848
	Lift Weight (lbs) 25' lengths	3,208	2,760	3,187	2,442	2,648	2,062	2,670		
EDDYTHREAD 40	0.D. (in)	1.295	1.650	1.900	2.375					
	I.D. (in)	1.083	1.418	1.645	2.123					
	Empty Weight (lb/ft)	1.461	2.070	2.547	3.308					
	Water Filled Weight (lb/ft)	1.860	2.754	3.468	4.842					
	C.R.R.	1.00	1.00	1.00	1.00					
	Pieces per Lift	70	51	44	30					
	Lift Weight (lbs) 21' lengths	2,148	2,217	2,353	2,084					
	Lift Weight (lbs) 24' lengths	2,454	2,534	2,690	2,382					
	Lift Weight (lbs) 25' lengths	2,557	2,639	2,802	2,481					
SCHEDULE 40	O.D. (in)	1.315	1.660	1.900	2.375	2.875	3.500	4.500		
	I.D. (in)	1.049	1.380	1.610	2.067	2.469	3.068	4.026		
	Empty Weight (lb/ft)	1.680	2.270	2.720	3.660	5.800	7.580	10.800		
	Water Filled Weight (lb/ft)	2.055	2.918	3.602	5.114	7.875	10.783	16.316		
	C.R.R.	1.00	1.00	1.00	1.00	1.00	1.00	1.00		
	Pieces per Lift	70	51	44	30	30	19	19		
	Lift Weight (lbs) 21' lengths	2,470	2,431	2,513	2,306	3,654	3,024	4,309		
	Lift Weight (lbs) 24' lengths	2,822	2,778	2,872	2,635	4,176	3,456	4,925		
	Lift Weight (lbs) 25' lengths	2,940	2,894	2,992	2,745	4,350	3,601	5,130		

